



## 全自动内焊机

automatic internal  
welding machine

## 全自动内焊机技术参数表

型号 MODEL	DPIWM 24 "	DPIWM 28 "	DPIWM 32 "	DPIWM 36 "	DPIWM 40 "
适用范围(mm) APPLICABLE RANGE	φ610-660	φ711-762	φ813-863	φ914-965	φ1016-1066
外形尺寸 (mm) PRODUCT DIMENSION	φ560X4220	φ650X4420	φ720X4345	φ850X4700	φ950X5300
压块数量 (个) NUMBER OF CLAMP SHOES	12X2	12X2	18X2	18X2	18X2
涨紧力 (T) EXPANDING FORCE	183	270	270	450	650
行走速度 (m/s) TRAVELLING SPEED	0~2.5	0~2.5	0~2.5	0~2.5	0~2.5
工作压力 (Mpa) WORKING PRESSURE	≤1.6	≤1.6	1.2	1.2	1.2
焊炬数量 (个) NUMBER OF WELDING TORCHES	4	4	4	4	6
送丝速度 (m/min) FEED RATE OF WELDING WIRE	8.5-10	8.5-10	8.5-10	8.5-10	8.5-10
适应壁厚 (mm) APPLICABLE THICKNESS	6-30	6-30	6-30	6-30	6-40
无线遥控行走 WIRELESS REMOTE CONTROL TO WALK	可选 OPTIONAL	可选 OPTIONAL	可选 OPTIONAL	可选 OPTIONAL	可选 OPTIONAL
重量 (Kg) WEIGHT	1030	1200	1350	1650	1850
型号 MODEL	DPIWM 44 "	DPIWM 48 "	DPIWM 52 "	DPIWM 56 "	DPIWM 60 "
适用范围 APPLICABLE RANGE	φ1117-1168	φ1219-1270	φ1320-1371	φ1422-1473	φ1524-1574
外形尺寸 (mm) PRODUCT DIMENSION	φ1050X5300	φ1200X5300	φ1270X5450	φ1320X5600	φ1500X5750
压块数量 (个) NUMBER OF CLAMP SHOES	18X2	18X2	24X2	24X2	24X2
涨紧力 (T) EXPANDING FORCE	750	750	750	750	750
行走速度 (m/s) TRAVELLING SPEED	0~2.5	0~2.5	0~2.5	0~2.5	0~2.5
工作压力 (Mpa) WORKING PRESSURE	1.2	1.2	1.2	1.2	1.2
焊炬数量 (个) NUMBER OF WELDING TORCHES	6	6	8	8	10
送丝速度 (m/min) FEED RATE OF WELDING WIRE	8.5-10	8.5-10	8.5-10	8.5-10	8.5-10
适应壁厚 (mm) APPLICABLE THICKNESS	6-40	6-40	6-40	6-40	6-40
无线遥控行走 WIRELESS REMOTE CONTROL TO WALK	可选 OPTIONAL	可选 OPTIONAL	可选 OPTIONAL	可选 OPTIONAL	可选 OPTIONAL
重量 (Kg) WEIGHT	2100	2300	2500	2600	2700